

Payment Kiosk


A16

Applications

Banking receipt printing
Photo&card vending
Insurance vending
Credit card payment
Utility bill collection
Information ads

Features

1. Powerful up-to-date CPU;
2. Waterproof IR/SAW touchscreen;
3. Zebra/CUSTOM branded printers;
4. 3DES EPP with motorized card reader;
5. Dye-sublimation photo printer;
6. High quality Cash validator
7. All steel sleek anti graffiti enclosure



Stereo audio

Barcode reader

Photo printer

19/17/15 inch water-proof SAW touchscreen

Metal EPP

Receipt printer

Motorized card reader

Cash validator

High performance host computer

UPS



Component/function layouts

Specifications

Model Name	A16B-C17NE	A16C-M19
Processor	3.0GHz Intel® Core™ i5 2320	3.0GHz Intel® Pentium™ E6600(fan)
RAM	4Gb DDR III(16G max)	2Gb DDR II(4G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof IR/SAW touchscreen	
Receipt printer	CUSTOM TG2480	CUSTOM TG2480
Photo printer	SHINKO 2145	
Metal EPP	MKP2920	
Cash validator	Cashcode MSM	MEI SCL83
List printer	(None)	Zebra TTP8200
Motorized card reader	Rm6 hybrid card reader for IC, Magnetic and M1 cards	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K1000 PRO UPS for at least 5 mins of power	
Audio	Bi-stereo channel 2X10W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM(totally 4-6 COMs) 2 USB2.0(totally 8-12 USBs) 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

