

# Touchscreen digital signage

## Digital Signage D34

### Applications

Museum  
Exhibition  
Apps store  
Presentation  
Information kiosk

### Features

1. Dual Core Intel CPU;
2. Full HD touchscreen monitor;
3. Full view angle IPS display;
4. WIFI and Camera optional
5. All steel anti-graffiti enclosure

### Component/function layouts



External antenna

32/37/42/47/55/65/70"  
FULL HD touchable IPS main monitor

All steel anti-graffiti enclosure stand



### Specifications

Part Name	D34A-32T	D34E-32T
Processor	Intel XEON E3-1225	Intel XEON E3-1225
RAM	8Gb DDR III(16G max)	8Gb DDR III(16G max)
HDD	500G 7200rpm 3.5" hard driver Up to 3TB size	
Display	32" LCD display	32" LCD display with DID LED backlight
Touchscreen	32" waterproof IR touchscreen	32" waterproof IR touchscreen
WIFI(optional)	Intel Integrated miniPCIe WIFI with external antenna	
Pen touch	Pen touch	
Rear I/O Connectors	Power Jack Fuse(3A) Power switch Host computer Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	WINDOWS XP/7/Linux 2.6 distribution(i.e. Fedora 9, CentOS 5, Ubuntu 10 and SUSE etc)	
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

CE FC

