



Applications

Bank cash deposit
Payment kiosk
Bank card cashless transaction

Features

1. Bundle notes deposit;
2. Wide temperature range PC;
3. High reliability component;
4. Dual color journal dot-matrix printer;
5. Integrated bank card reader;
6. UL291 standard safe with Le Guard lock

Lift point

Specfications

| | |
|-----------------------|--|
| Model Name | AW37BN100 |
| Processor | Intel® XEON E1265L V3 |
| RAM | 4Gb DDR III(16G max) |
| HDD | 60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size |
| Monitor | 15" LCD with DX9 decoding acceleration |
| Touchscreen | Water proof Capacitive/IR/SAW touchscreen |
| Receipt printer | CUSTOM®(Italy brand) TG2480II thermal printer |
| Payment card reader | Motorized IC, magnetic and NFC/RFID card reader |
| Journal printer | 90in stylus impact dual color printer Mp912 |
| Metal PINPAD | 16 key metal EPP |
| Cash acceptor | Cash deposit bank notes acceptor |
| Surveillance | 4 way HDD camera system |
| UPS | 1000VA UPS |
| Audio | Bi-stereo channel 2X5W speakers |
| Enclosure | Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Safe with security lock and handle Moistureproof,Antirust,Anti-acid,Static free Dimensions: 80-120cm *80-96cm * 182-216cm |
| Rear I/O Connectors | Power Jack Fuse(6A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45 |
| Fans | 110 or 220 V AC selective Operation noise level: <45dB |
| Power consumption | 110V AC or 220V AC(with fans) 50-60Hz 3A |
| Operating System | XP, WIN 7,WIN8, WIN10, XPe, WES |
| Operating Temperature | -20°C up to 55°C(need heater in below 0°C environment) |
| Operating Humidity | 0% ~ 95% (relative humidity; non-condensing) |

Component/function layouts

