

AD11 dual screen bank account inquiry and passbook printing touchscreen kiosk


Dualscreen banking kiosk AD11

Applications

Passbook printing
A4 bank account list printing
Check validation
Receipt printing
Utility bill collection
Information ads

Features

1. Powerful up-to-date CPU;
2. Waterproof CA/IR/SAW touchscreen;
3. High quality bank passbook printers;
4. Check validator;
5. Fast A4 thermal list printer;
6. CUSTOM receipt printer
7. All steel sleek anti graffiti enclosure



19 inch ads display screen(no touch)

PIN hole camera
Coin mechanism

17/15 inch water-proof PCAP touchscreen

ID card reader

Thermal receipt printer

Check validator

Coin out

A4 list printer

Cash acceptor

Stereo audio



Component/function layouts

Specifications

Model Name	AD11MTPN17-3	AD11APN-MS19
Processor	3.1GHz Intel® XEON™ E3-1285L V3(fan)	3.1GHz Intel® XEON™ E3-1285L V3(fan)
RAM	4Gb DDR III(16G max)	4Gb DDRIII(4G max)
HDD	64G SSD and 500G 7200rpm 3.5" hard driver	
	Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof CA/IR/SAW touchscreen	
Ads display	19" AUO LCD	19" AUO LCD
Dotmatrix printer	Nantian PR9E passbook printer	
Receipt printer	CUSTOM TG2480	CUSTOM TG2480
Cash acceptor(optional)	CASHCODE SM	MEI SC83L
A4 List printer	KPM216	KM216
Credit card reader	MAGTEK	
Coin mechanism	NRI C2	NRI G13+MK4
Check validator	MAGTEK MICR	
ID card reader	RD188K	
Camera	Pinhole camera PH2	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K1000 PRO UPS for at least 15 mins of power	
Audio	Bi-stereo channel 2X3W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6/3.1, Ubuntu, Fedora	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

