



Barcode reader

UPS(inside)



17/19/22 inch LCD display for advertisement

19/17/15 inch water-proof PCAP touchscreen

Stereo audio

Metal keyboard and EPP

Thermal printer

Cash acceptor

Metal EPP

SIM card Dispenser

High performance host computer

**Component/function layouts****Applications**

Member card printing
Voucher& Redemption
Large cash break
Bitcoin redemption
Passport ID&member registration
Information ads
Points, comp balance inquiry
Gaming regulation display
Prompt information display
Interactive play games

Features

1. Powerful up-to-date CPU;
2. Waterproof CA touchscreen;
3. ID card reader;
4. SIM card dispenser;
5. High quality Cash validator/accepter
6. All steel sleek anti graffiti enclosure

Specifications

Model Name	AD16MT
Processor	3.0GHz Intel® Core™ i7
RAM	4Gb DDR III(16G max)
HDD	128G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size
Advertisement LCD	21.5" LCD with DX12
Operation monitor	19" LCD with DX12
Touchscreen	Water proof PCAP touchscreen
Receipt printer	80mm thermal printer
ID card reader	IDV passport OCR image reader
Card Dispenser	SIM card dispenser
Metal PC keyboard	MKT2752
Barcode reader	(none)
Metal EPP	MKP2920
Cash validator	High speed cash acceptor
3G/GPRS Modem(optional)	GPRS dual band SMS modem
UPS	UPS for at least 5 mins of power
Audio	Bi-stereo channel 2X5W speakers
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM(totally 4-6 COMs) 2 USB2.0(totally 8-12 USBs) 1 GbE LAN RJ45
Fans	110 or 220 V AC selective Operation noise level:<45dB
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)

