


A4 laser printer      HP LaserJet1008 laser printer

RFID reader	ZKTEK R3
Ticket printer	ZKTEK P58C thermal printer, thickness:80-110g/m2(optional)
Credit/Debit card R'	ZKTEK R1
EPP metal keypad(optional)	

GPRS Modem	Simemse MC55 GPRS dual band SMS modem
UPS	SANTAK K500 PRO UPS for at least 5 mins of power
Audio	Bi-stereo channel 2X10W speakers

Barcode reader      HONEYWELL® 4823F 1D Laser Reader (None)



### Applications

Bank cash recycling system  
Bitcoin redemption ATM  
Transaction CRS

### Features

1. Bundle notes recycling and escrow;
2. Extremely wide temperature range PC;
3. High reliability component;
4. Fastest bill recycler with shutter;
5. Dual color journal dot-matrix printer;
6. Independent surveillance system
7. UL291 standard safe

### Lift point

### Specifications

Model Name	AW91DBRM10
Processor	Intel® i5 processor
RAM	4Gb DDR III(16G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size
Monitor	15" LCD with DX9 decoding acceleration
Touchscreen	15" Water proof Capacitive/IR touchscreen
Receipt printer	thermal printer, thickness:80-120g/m2(optional)
Payment card reader	Motorized IC, magnetic and RFID card reader
Journal printer	9pin stylus impact dual color printer Mp912
Metal PINPAD	ZKTEK MKP2920SEA
Cash dispenser	Glory BRM10 friction cash recycling module with 7-10mm thickness UL291 safe
Surveillance	4 way HDD camera system
UPS	Rackmount 1U 1150VA UPS
Audio	Bi-stereo channel 2X5W speakers
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Safe with security lock and handle Moistureproof,Antirust,Anti-acid,Static free Dimensions: 120-180cm *80-96cm * 182-216cm

Rear I/O Connectors	Power Jack Fuse(6A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45
Fans	110 or 220 V AC selective Operation noise level: <45dB
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A
Operating System	XP, WIN 7,WIN8, WIN10, XPe, WES
Operating Temperature	0°C up to 55°C(need heater in below 0°C environment)
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)

